

Datei:Mercury 8.pdf

Basisinformationen

Anzeigetitel	Datei:Mercury 8.pdf																														
Standardsortierschlüssel	Mercury 8.pdf																														
Seitenlänge (in Bytes)	226																														
Namensraum	Datei																														
Seitenkennnummer	1035																														
Seiteninhaltssprache	de-formal - Deutsch (Sie-Form)																														
Seiteninhaltsmodell	Wikitext																														
Indizierung durch Suchmaschinen	Erlaubt																														
Anzahl der Weiterleitungen zu dieser Seite	0																														
Prüfsummenwert	67511f283d0a2d480870ceddee887f8c5532b172																														
Seitenbild	 Mercury 8 Alphanumeric Pager FEATURES 8 Line Alphanumeric Display 21 Characters per Line - Zooms to 4 Lines With 17 Characters per Line 8 Call Code Addresses - Button Activated Display Lighting - Message Capacity of 80 Messages - Up to 500 Characters per Message - Practical Alarm Feature - Time and Date Stamp Added on Message Receipt - Automatic Detection and Rejection of Duplicate Messages 11 Selectable Languages 4 Selectable Alert Tones - Windows PC Software Programmable or Exclusive Features Via Pager Buttons 700 Hours of Battery Life on a Single AAA Alkaline SPECIFICATIONS <table><tr><td>Dimensions (Without Holder)</td><td>75 (L) x 51 (W) x 18 (H) mm</td></tr><tr><td>Weight</td><td>2.9 (L) x 2.0 (W) x 0.7 (H) inches</td></tr><tr><td>Battery</td><td>1 x AAA alkaline</td></tr><tr><td>Approx. Battery Life</td><td>700 hours</td></tr><tr><td>Frequencies Covered</td><td>135-175 MHz 275-297 MHz 406-476 MHz 915-930 MHz</td></tr><tr><td>Signal Transmission Type</td><td>POCSAG (CDR)</td></tr><tr><td>Channel Spacing</td><td>VHF: 9kHz / 2.5kHz / 6.25kHz UHF: 4kHz / 5kHz / 12.5kHz 300MHz: 10kHz / 12.5kHz</td></tr><tr><td>Data Transmission Rate</td><td>51bps, 1200bps or 2400bps</td></tr><tr><td>Modulation System</td><td>Carrier Frequency Shift Keying (NFS)</td></tr><tr><td>Frequency Deviation</td><td>±4.5kHz</td></tr><tr><td>Receiving Sensitivity</td><td>512 lps 5uV/m, 1200bps 7uV/m, 2400bps 8uV/m</td></tr><tr><td>Selectivity</td><td>65db ±25kHz</td></tr><tr><td>Spurious Rejection</td><td>60dB+</td></tr><tr><td>Frequency Stability</td><td>10ppm (V-F) 5ppm (L-F) 3ppm (R30 MHz)</td></tr><tr><td>Storage Temperature / Humidity</td><td>0°C/30% to 50°C/100% at 95% humidity (noncondensing)</td></tr></table> Deutschland / Germany HMK GmbH Distribution Obere Zeil 4 61440 Oberursel HMK COMMTECH WIRELESS	Dimensions (Without Holder)	75 (L) x 51 (W) x 18 (H) mm	Weight	2.9 (L) x 2.0 (W) x 0.7 (H) inches	Battery	1 x AAA alkaline	Approx. Battery Life	700 hours	Frequencies Covered	135-175 MHz 275-297 MHz 406-476 MHz 915-930 MHz	Signal Transmission Type	POCSAG (CDR)	Channel Spacing	VHF: 9kHz / 2.5kHz / 6.25kHz UHF: 4kHz / 5kHz / 12.5kHz 300MHz: 10kHz / 12.5kHz	Data Transmission Rate	51bps, 1200bps or 2400bps	Modulation System	Carrier Frequency Shift Keying (NFS)	Frequency Deviation	±4.5kHz	Receiving Sensitivity	512 lps 5uV/m, 1200bps 7uV/m, 2400bps 8uV/m	Selectivity	65db ±25kHz	Spurious Rejection	60dB+	Frequency Stability	10ppm (V-F) 5ppm (L-F) 3ppm (R30 MHz)	Storage Temperature / Humidity	0°C/30% to 50°C/100% at 95% humidity (noncondensing)
Dimensions (Without Holder)	75 (L) x 51 (W) x 18 (H) mm																														
Weight	2.9 (L) x 2.0 (W) x 0.7 (H) inches																														
Battery	1 x AAA alkaline																														
Approx. Battery Life	700 hours																														
Frequencies Covered	135-175 MHz 275-297 MHz 406-476 MHz 915-930 MHz																														
Signal Transmission Type	POCSAG (CDR)																														
Channel Spacing	VHF: 9kHz / 2.5kHz / 6.25kHz UHF: 4kHz / 5kHz / 12.5kHz 300MHz: 10kHz / 12.5kHz																														
Data Transmission Rate	51bps, 1200bps or 2400bps																														
Modulation System	Carrier Frequency Shift Keying (NFS)																														
Frequency Deviation	±4.5kHz																														
Receiving Sensitivity	512 lps 5uV/m, 1200bps 7uV/m, 2400bps 8uV/m																														
Selectivity	65db ±25kHz																														
Spurious Rejection	60dB+																														
Frequency Stability	10ppm (V-F) 5ppm (L-F) 3ppm (R30 MHz)																														
Storage Temperature / Humidity	0°C/30% to 50°C/100% at 95% humidity (noncondensing)																														

Seitenschutz

Bearbeiten	Alle Benutzer (unbeschränkt)
Verschieben	Alle Benutzer (unbeschränkt)
Hochladen	Alle Benutzer (unbeschränkt)

[Das Seitenschutz-Logbuch für diese Seite ansehen.](#)

Versionsgeschichte

Seitenersteller	OE1CMW (Diskussion Beiträge)
Datum der Seitenerstellung	12:10, 2. Mär. 2010
Letzter Bearbeiter	OE1CMW (Diskussion Beiträge)
Datum der letzten Bearbeitung	12:10, 2. Mär. 2010
Gesamtzahl der Bearbeitungen	1
Gesamtzahl unterschiedlicher Autoren	1
Anzahl der kürzlich erfolgten Bearbeitungen (in den letzten 90 Tagen)	0
Anzahl unterschiedlicher Autoren der kürzlich erfolgten Bearbeitungen	0